

Premier 5

The decorative textured finish
for ceilings and walls

PM25 & PR12

HOT OR COLD MIX STAYS WORKABLE FOR LONGER

- ✓ Easy to work with, mixes easily and slides on, saving time
- ✓ Same day process saves time and travel
- ✓ Covers and hides uneven surfaces
- ✓ A greater coverage per bag
- ✓ Gives a professional finish time after time



General Information

Premier 5 is a hot or cold mix decorative textured finish for use on ceilings and walls.

Authority

Premier 5 conforms to:

- Manufactured to BS6214: 1982

Coverage

As a general guide: Light textures 35m² / 25kg
Heavy textures 20-30m² / 25kg

Surface Preparation

All surfaces must be clean, sound and dry prior to application. For application on papered, flaky or distempred surfaces, remove previous decorative material and seal, using Wondertex Stabiliser.

Mixing

Slowly add **Premier 5** to hot, warm or cold water at about 1kg per pint (approx.500ml). Stir in briskly and leave for a few minutes. Mix to the required consistency by adding more. Always leave **Premier 5** to stand for a few minutes before application. Do not use below 3°C.

Application and fixing

Apply liberally in one metre strips with brush or roller across the ceiling width or from top to bottom of walls. Texture an area of approximately one square metre at a time while still wet. Working time is up to 15 minutes.

Application to plasterboard

Tape using white perforated tape – Apply paste to the joints and to 50mm either side. Press tapes firmly over joint with caulking tool. At this stage a light pre-caulk of the tapes is recommended. To produce a surface of uniform porosity the recommended method is to carry out full joint treatment, allow to dry, and texture as a one-day operation.

Caulking and texturing

Caulk out taping and pre-caulking with caulk tool. After approximately 2 hours, apply texture coat with a laying-on brush or lambswool roller and pattern to required design. Leave to dry completely for 5 days, apply a mist coat and full coat of good quality emulsion paint for the perfect finish.

Should weather or site conditions cause uneven drying, any resulting colour irregularities can be treated simply by painting over with an almond white emulsion diluted with 25% water.

Where texturing may be delayed for an unusually long period, sealing should be carried out as soon as possible – particularly if the weather is hot and dry. To produce a surface of uniform porosity the recommended method is to carry out taping, pre-caulking, caulking and texturing as a one-day operation.

Pattern application

Wondertex manufacture a comprehensive range of professional tools and accessories for creating and finishing the many decorative effects available. A pattern range leaflet can be obtained from the address overleaf.

Packaging

Supplied in powder form in 12.5kg bags or 25kg bags.

Storage

Recommended shelf life 12 months. Store in dry conditions.

Health & Safety

Avoid contact with eyes and ingestion. If splashes enter eyes DO NOT RUB but wash with plenty of water. It is advisable to wear protective gloves and wash off any contact with skin. Wash hands after use. Clean any accidental splashes from floors etc. with warm water before dry.

Health and safety data sheets for all Wondertex products can be obtained from the address below.

Other products

Wondertex Premier Smooth 25kg

Wondertex Decorators Premier Filler 10kg

Wondertex Plasterboard Sealer 20 litre & 5 litre bucket

Wondertex White joint tape 150 metre roll

Full Range of Tools and Accessories

Tools and accessories

Code	Description	Size
BLBR	Laying on brush – block	6 inch
FLBR	Laying on brush – flat	7 inch
DYSB	Stipple brush DIY	150 x 100 (6 inch x 4 inch)
HS06	Stipple brush Trade	150 x 100 (6 inch x 4 inch)
HS08	Stipple brush Trade	200 x 150 (8 inch x 6 inch)
HS13	Stipple brush Trade	325 x 325 (13 inch x 13 inch)
BL PAD	Broken leather pad – with handle	200 x 150 (8 inch x 6 inch)
PA PAD	Broken leather pad – with pole attachment	200 x 150 (8 inch x 6 inch)
PLSR	Rollers – stipple effect	
PLBR	Rollers – bark effect	
PLDR	Rollers – diamond effect	
DGRO	Rollers – diagonal effect	
CO12	Comb	300 (12 inch)
CO10	Comb	250 (10 inch)
CO08	Comb	200 (8 inch)
CO04	Comb	100 (4 inch)
CBRO	Comb – rose	Small
CBFL	Comb – flower	Large
HYBRID	Hybrid combs (pack of 4)	
TLACE	Lacer	Large (single)
LACE	Lacer	Small (with backing)
PLCO	Comb for DIY	
PLCA	Caulker for DIY	
CA12	Caulker	300 (12 inch)
CA10	Caulker	250 (10 inch)
CA08	Caulker	200 (8 inch)
EB25	Mixing bucket	25L
BU01	Mixing bumper head	
WS20	Sealer – white	20L
SEWH	Sealer – white	5L
ST05	Stabiliser	5L

Note: All 'Wondertex' products are of high quality, being subjected to rigid quality control. 'Wondertex', however, cannot govern conditions of applications and usage, thus any warranty written or implied is given in good faith, but covers materials only. Wondertex will not accept any responsibility for damage or injury arising from the storage, handling, application or use of its products.