

# Premier Filler

A multi purpose filler for decorators, builders and jointers

PF10

## MIX WITH COLD WATER

- ✓ Sets in 90 minutes
- ✓ For most plasters & plasterboards
- ✓ Less shrinkage
- ✓ Easy to sand
- ✓ Dries to a hard finish

## General Information

**Premier Filler** is a Class B gypsum-based 90 minute setting compound. A decorator's filler for most plasters and plasterboards. For filling and finishing plasterboard joints. For smoothing over unwanted textured surface.

## Authority

**Premier Filler** conforms to:

- Manufactured to BS6214: 1982.
- For use on all gypsum boards conforming to BS1230 Part 1 1985.

## Coverage

Refer to manufacturer.

## Surface Preparation

All surfaces must be clean, sound and dry prior to application, any loose or flaky material must be removed.

Seal any porous surface using Wondertex Stabiliser.



## Mixing

Always use clean water. Suggested ratio mix for **Premier Filler** is 1 part water to 1.75 parts powder. Stir continuously until free from lumps. Allow to soak for 10 minutes. Mix again prior to use. Do not use below 3°C.

## Application

For Decorators and Builders. Use a caulker or a filler knife with the **Premier Filler** to smooth over desired areas. Deeper indentations may need two applications. Workable for 60 minutes. Sand to a smooth surface when dry.

## For Tapers and Jointers

For hand application only. **Premier Filler** is applied to the trough of the tapered edge joints, centre jointing tape over the joint and press down with jointing knife with sufficient pressure to free any trapped air bubbles, and leave sufficient joint filler under the tape to ensure good adhesion. Immediately after the tape has been fixed apply a new layer of joint filler over the tape flush with the surface of the plasterboard, before the **Premier Filler** begins to stiffen. After approximately 90 minutes, a finishing application should be applied to obtain complete elimination of tape edges. The jointers slurry sponge should be moistened and any surplus material wiped from the edges of the joint, leaving a smooth finish.

## To smooth over unwanted textures

### Step 1

Apply sufficient mixed Premier Filler to cover the surface using a caulker or plasterers trowel. Do not apply to an area greater than 1m<sup>2</sup> at a time and repeat this process until the ceiling/wall is completed.

### Step 2

Return to the original area covered within 20-30 minutes to complete finishing by splashing the area using a wet paint brush and smoothing over using a caulker or plasterers trowel to achieve a smooth, flat finish.

### Step 3

In most applications one coat of Premier Filler is sufficient, however where a second coat is required it should be applied immediately, using the same process, once first coat is firm to the touch.

## Packaging

Supplied in powder form in 10kg paper sacks.

## Storage

Recommended shelf life 6 months. Store in dry conditions.

## Health & Safety

Avoid contact with eyes and ingestion. If splashes enter eyes DO NOT RUB but wash with plenty of water. It is advisable to wear protective gloves and wash off any contact with skin. Wash hands after use. Clean any accidental splashes from floors etc. with warm water before dry.

Health and safety data sheets for all Wondertex products can be obtained from the address below.

## Other products

Wondertex Premier 5 texture 25kg & 12.5kg

Wondertex Premier Smooth 25kg

Wondertex Plasterboard Sealer 20 litre & 5 litre bucket

Wondertex White joint tape 150 metre roll

Full Range of Tools and Accessories

## Tools and accessories

Code	Description	Size
CA12	Caulker	300 (12 inch)
CA10	Caulker	250 (10 inch)
CA08	Caulker	200 (8 inch)
EB25	Mixing bucket	25L
BU01	Mixing bumper head	20L
WS20	Sealer – white	5L
SEWH	Sealer – white	5L
ST05	Stabiliser	

Note: All 'Wondertex' products are of high quality, being subjected to rigid quality control. 'Wondertex', however, cannot govern conditions of applications and usage, thus any warranty written or implied is given in good faith, but covers materials only. Wondertex will not accept any responsibility for damage or injury arising from the storage, handling, application or use of its products.